


DRAWINGS (Unit: mm)

ELECTRICAL CHARACTERISTICS (STC)

Module Type: TH***PMB7-46SCF	445	440	435	430	425	420
Maximum Power: P _{max} [W]	445	440	435	430	425	420
Open Circuit Voltage: Voc [V]	43.8	43.7	43.6	43.5	43.4	43.3
Short Circuit Current: Isc [A]	13.01	12.90	12.79	12.68	12.56	12.46
Voltage at Maximum Power: V _{mp} [V]	36.4	36.3	36.2	36.1	36.0	35.9
Current at Maximum Power: I _{mp} [A]	12.23	12.13	12.02	11.92	11.81	11.71
Module Efficiency: η [%]	21.4	21.1	20.9	20.7	20.4	20.2

ELECTRICAL CHARACTERISTICS (NMOT)

	335	331	328	324	320	316
Maximum Power: P _{max} [W]	335	331	328	324	320	316
Open Circuit Voltage: Voc [V]	41.8	41.7	41.6	41.5	41.4	41.3
Short Circuit Current: Isc [A]	10.50	10.41	10.32	10.23	10.14	10.05
Voltage at Maximum Power: V _{mp} [V]	34.7	34.6	34.5	34.4	34.3	34.2
Current at Maximum Power: I _{mp} [A]	9.66	9.57	9.49	9.41	9.32	9.24

- Standard Test Conditions (STC): irradiance 1000 W/m², AM 1.5; ambient temperature 25°C according to EN 60904-2
- Nonlinear Module Operating Temperature (NMOT): irradiance 800W/m²; wind speed 3m/s; ambient temperature 20°C
- Tolerance of P_m: 0~±5W; Measuring uncertainty of power: ±3%; Performance deviation of Voc [V], Isc [A], V_{mp} [V] and I_{mp} [A]: ±2%

TEMPERATURE PARAMETERS



NMOT	42.30 °C (±2°C)
Temperature Coefficient of Voc	-0.27%/°C
Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of P _m	-0.34%/°C

MAXIMUM RATINGS

Maximum System Voltage [V]	DC1500 (IEC)
Series Fuse Rating [A]	25
Maximum Surface Load Capacity [Pa]	Front 5400 / Back 2400
Temperature Range [°C]	-40 ~ +85
Withstanding Hail	Maximum diameter of 25mm with impact speed of 23m/s

MECHANICAL PARAMETERS

Dimensions	1899 × 1096 × 30mm
Weight	21.8kg
Front glass	tempered glass, 3.2mm
Frame	Anodized aluminum profile
Cells	Mono-crystalline solar cell
Cell Orientation	320 (64 × 5)
Junction Box	IP68, two diodes
Cable	4mm ² , +300mm/-1000mm(Vertical), +220mm/-180mm(Horizontal)
Packaging	36pcs/box; 864pcs/40'container; 1296pcs/flat car

WARRANTY
Linear Power Output Warranty

I-V CURVE

CERTIFICATIONS
Quality Management System and Product Certification

IEC61215/61730, IEC62804(PID), IEC61701(Salt),
IEC62716 (Ammonia), IEC60068-2-68(Sand)
ISO 9001:2015 / quality management system
ISO 14001:2015 / environmental management system
ISO 45001:2018 / occupation health safety management system
ISO 50001:2011 / energy management system
IEC TS 62991—2016 / PV industry quality management system

